




Single span carrier with uniaxial bending

• F_1 at $f = L/200$

1 Single load



MIQ-90



MIQ-90

span width [cm]	F [kN]	f [mm] $\leq L/200$	F [kN]	f [mm] $\leq L/200$
25	77.22	0.1	64.30	0.1
50	38.59	0.4	32.14	0.4
75	25.71	0.9	21.41	0.9
100	19.26	1.6	16.04	1.6
125	15.39	2.5	12.81	2.5
150	12.81	3.5	10.65	3.5
175	10.96	4.8	9.11	4.8
200	9.57	6.3	7.95	6.3
225	8.48	8.0	7.05	8.0
250	7.62	9.9	6.32	9.9
275	6.90	12.0	5.73	12.0
300	6.31	14.2	5.23	14.3
325	5.63	16.3	4.66	16.3
350	4.82	17.5	3.98	17.5
375	4.16	18.8	3.43	18.8
400	3.62	20.0	2.98	20.0
425	3.17	21.3	2.60	21.3
450	2.79	22.5	2.28	22.5
475	2.46	23.8	2.01	23.8
500	2.18	25.0	1.77	25.0
525	1.94	26.3	1.57	26.3
550	1.73	27.5	1.39	27.5
575	1.55	28.8	1.24	28.8
600	1.38	30.0	1.10	30.0